

Open VPN manual

1.	TLS client to client	2
	1.1. Download software	2
	1.2. Installing software	2
	1.3. Creating certificates	2
	1.4. Configure RUT500 as an OpenVPN Tls server	4
	1.5. Configure RUT500 as an OpenVPN Tls client	7
	1.6. Configure Computer as an OpenVPN Tls server	8
	1.7. Configure Computer as an OpenVPN Tls client	g
2.	Static key	10
	2.1. Configure your computer as a client	10
	2.2. Configure RUT500 as a server	11
	2.3. Connect to server	



1. TLS client to client

1.1. Download software

1.1.1. Download "OpenVPN windows installer" 64bit or 32bit software. (http://openvpn.net/index.php/open-source/downloads.html)

1.2. Installing software

- 1.2.1. Press "Next"
- 1.2.2. Press "I Agree"
- 1.2.3. If you want to create certificates using this computer check "OpenSSL Utilities" and "OpenVPN RSA Certificates Management Scripts" checkboxes (should be checked all boxes) otherwise leave default settings.



- 1.2.4. Press "Install" and wait for installation to complete.
- 1.2.5. Press "Next"
- 1.2.6. Press "Finish"

1.3. Creating certificates

- 1.3.1. Open cmd.exe (Start->Run->cmd.exe)
- 1.3.2. If you installed OpenVPN in default folder write
 "cd \Program Files\OpenVPN\easy-rsa" otherwise use your created file tree.
- 1.3.3. If you doing it for the first time write command "init-config" it will reset all certificate system. (if you have already created certificates on this computer and if you don't want to recreate all your certificates skip this step.)
- 1.3.4. This step is optional (It will help to create certificates easier because you are creating hint for the certificate data). A new file will appear C:\OpenVPN\easyrsa\vars.bat. Open it with your favorite text editor like notepad and edit these lines:



After that save and close vars.bat file.

```
set KEY_COUNTRY= your_text_1
set KEY_PROVINCE= your_text_2
set KEY_CITY= your_text_3
set KEY_ORG= your_text_4
set KEY_EMAIL= your_text_5
```

1.3.5. To build root keys write these commands in cmd.exe: "vars", "clean-all", "build-ca". Now you will be asked to write information (one line at the time) about your certificate:

```
Country Name (2 letter code) [US]:us
State or Province Name (full name) [CA]:ca
Locality Name (eg, city) [SanFrancisco]:san
Organization Name (eg, company) [OpenUPN]:name
Organizational Unit Name (eg, section) [changeme]:name
Common Name (eg, your name or your server's hostname) [changeme]:<mark>Unique_name</mark>
Name [changeme]:name
Email Address [mail@host.domain]:email@company.com
```

Only "Common Name (eg, your name or your server's hostname) [changeme]:" is important because it must be unique name.

Now you have new file in your C:\OpenVPN\easy-rsa\keys catalog - "ca.crt"

This step should be done once and created file must be used in server and all clients' settings.

1.3.6. To create server certificate write these commands in cmd.exe: "vars", "build-key-server server". Now you will be asked to write information (one line at the time) about your certificate:

```
Country Name (2 letter code) [US]:us
State or Province Name (full name) [CA]:ca
Locality Name (eg, city) [SanFrancisco]:san
Organization Name (eg, company) [OpenUPN]:open
Organizational Unit Name (eg, section) [changeme]:name
Common Name (eg, your name or your server's hostname) [changeme]:Unique_name_2
Name [changeme]:name
Email Address [mail@host.domain]:mail
Please enter the following 'extra' attributes
to be sent with your certificate request
A challenge password []:password
An optional company name []:name
```

Only "Common Name (ex. your name or your server's hostname) [changeme]:" (it must be unique) and "A challenge password []" (you'll have to use it in all clients certificates) are important.

After that you will be asked to agree, press "y" and "enter" two times.

Now you have new files in your C:\OpenVPN\easy-rsa\keys catalog – "server.crt" and "server.key".

1.3.7. To create Diffie Hellman file write to cmd.exe: "build-dh". Now you have new file in your C:\OpenVPN\easy-rsa\keys catalog - "dh1024.pem" (This is the last file required for server configuration).



1.3.8. To create Client certificate files write to cmd.exe: "vars", "build-key <desired unique remote user name>" (the same user name will be used in certificate data). Now you will be asked to write information (one line at the time) about your certificate:

```
Country Name (2 letter code) [US]:us
State or Province Name (full name) [CA]:ca
Locality Name (eg, city) [SanFrancisco]:sa
Organization Name (eg, company) [OpenUPN]:op
Organizational Unit Name (eg, section) [changeme]:uni
Common Name (eg, your name or your server's hostname) [changeme]:unique
Name [changeme]:name
Email Address [mail@host.domain]:mail
Please enter the following 'extra' attributes
to be sent with your certificate request
A challenge password []:password
An optional company name []:name
```


Only "Common Name (eg, your name or your server's hostname) [changeme]:" (it must be unique and the same as in command you entered in cmd.exe <desired unique remote user name>) and "A challenge password []" (you'll have to use it in all clients certificates) are important. After that you will be asked to agree, press "y" and "enter" two times. Now you have new files in your C:\OpenVPN\easy-rsa\keys catalog – "unique.crt and "unique.key".

1.4. Configure RUT-500 as an OpenVPN Tls server

- 1.4.1. Open RUT500 web GUI and select services -> OpenVPN
- 1.4.2. Create new configuration file by selecting role "server" and typing configuration name which you like. Then press Add New button.



1.4.3. After that you will see a line with your tunnel. Press edit button to configure server.





1.4.4. On the opened page you will see Main Settings. After configuring press save at the bottom of the page.


Main settings					
Enable	Check this I	oox if you wan	t to e	enable OpenVPN service	
Port	t 1194			Default OpenVPN port	
	TCP/UDP port for both, local and remote				
LZO	V			Check this box if you want to enable data compresion (to save data bandwidth) Choose TIs for multiple clients	
Authentication					
Client to client	Allow clie	ent-to-client trafl	Check this box if you want that clients could be flic able to connect to each other		
Keep alive	10 120			Leave default	
	Helper directi	ive to simplify th	he expression ofping andping-restart in server mod		
Virtual network IP address	10.8.0.0		Your virtual network ip adress. You can change only second value 10.x.0.0		
Virtual network netmask	255.255.255.0			se 255.255.255.0 network netmask	
Certificate authority	Pasirinkti failą	ca.crt	In e	ach upload box, choose to upload files	
Server certificate	Pasirinkti failą	server.crt		n example from your	
Server key	Pasirinkti failą	server.key	C:\P cata	rogram Files\Open\/PN\easy-rsa\keys	
Diffie Hellman parameters	Pasirinkti failą	dh1024.pem	caca	108	

1.4.5. By default everyone who connects to the server will be able to connect to each other by virtual IP address, but if you want to connect to their local IP address you must add client by writing its' name (recommend to write its' unique name) and pressing "add".





1.4.6. Configure client settings as in picture below and press "save" at the bottom of the page after configuring client settings.



You have to choose virtual local/endpoint from these paired IP endings.

```
5,
                 6] [
                       9, 10] [ 13, 14]
                                        [ 17, 18]
         [ 25, 26] [ 29, 30] [ 33, 34] [ 37, 38]
  21, 22]
         [ 45, 46] [ 49, 50] [ 53, 54] [ 57, 58]
 41, 42]
         [ 65, 66] [ 69, 70] [ 73, 74] [ 77, 78]
 61, 62]
[81, 82] [85, 86] [89, 90] [93, 94] [97, 98]
[101,102] [105,106] [109,110] [113,114] [117,118]
[121,122] [125,126] [129,130] [133,134] [137,138]
[141,142] [145,146] [149,150] [153,154] [157,158]
[161,162] [165,166] [169,170] [173,174] [177,178]
[181,182] [185,186] [189,190] [193,194] [197,198]
[201,202] [205,206] [209,210] [213,214] [217,218]
[221,222] [225,226] [229,230] [233,234] [237,238]
[241,242] [245,246] [249,250] [253,254]
```




1.5. Configure RUT-500 as an OpenVPN Tls client


- 1.5.1. Open RUT500 web GUI and select services -> OpenVPN
- 1.5.2. Create new configuration file by selecting role "client" and typing configuration name (we recommend to write same unique name as in certificate (CN)). Then press Add New button.



1.5.3. Now press "edit" button.



1.5.4. Fill forms as in example and press save.





1.6. Configure Computer as an OpenVPN Tls server

1.6.1. In "C:\Program Files\OpenVPN\config" create file "server.opvn" which contains these settings:

```
## server.ovpn ##
port 1194
proto udp
dev tun
ca ca.crt
cert server.crt
key server.key
dh dh1024.pem
server 10.8.0.0 255.255.255.0
ifconfig-pool-persist ipp.txt
keepalive 10 120
comp-lzo
persist-key
persist-tun
status openvpn-status.log
verb 3
```

Firstly choose your server virtual IP address "10.x.0.0" default is 10.8.0.0, then decide whether you need or not need to use data compression. If you need it leave "comp-lzo" if don't - delete it.

- 1.6.2. In 1.6.1. settings you can see four names highlighted in green. These files should be copied in "C:\Program Files\OpenVPN\config" (the same folder as server config file).
- 1.6.3. To create client with static virtual ip, create file with unique client name for example: "unique" and put content in it as in this example:

```
ifconfig-push 10.8.0.10 10.8.0.9
iroute 192.168.2.0 255.255.255.0
push route 192.168.99.0 255.255.255.0
push route 192.168.3.0 255.255.255.0
```

- 1.6.3.1. In the first line write virtual local and endpoint address as in 1.4.6 example.
- 1.6.3.2. In the second line write this client (which you are configuring now) subnet address and mask address.



- 1.6.3.3. In the third line write server subnet address with mask address
- 1.6.3.4. In the fourth and other lines write other clients subnet addresses and mask addresses (if you want enable client to connect to these clients subnets), for example: If you have server with subnet 192.168.2.0 and three clients which have subnets like: 192.168.3.0, 192.168.4.0, 192.168.5.0. You configuring client with 192.168.3.0 and want to give him 10.8.0.150 virtual address your configure should look like this:

ifconfig-push 10.8.0.150 10.8.0.149 iroute 192.168.3.0 255.255.255.0 push route 192.168.2.0 255.255.255.0 push route 192.168.4.0 255.255.255.0 push route 192.168.5.0 255.255.255.0

1.7. Configure Computer as an OpenVPN Tls client

In "C:\Program Files\OpenVPN\config" create file "unique.opvn" which contains these settings:

```
## remote.ovpn ##
client
dev tun
proto udp
remote 192.168.99.151 1194
resolv-retry infinite
nobind
persist-key
persist-tun
ca ca.crt
cert unique.crt
key unique.key
comp-lzo
verb 3
route-delay
```



In line starting with "remote" write your server IP address and port (port is usually default 1194).

Files with name highlighted in green should be placed in "C:\Program Files\OpenVPN\config" (the same folder as client config file).


After that open application "OpenVPN GUI". It should be already installed in your computer as bundle of "OpenVPN windows installer". Then you will see this "

" two computers with red displays. Press on it with right mouse button and select "Connect".

2. Static key

2.1. Configure your computer as a client

- 2.1.1. Start "Generate a static OpenVPN key" shortcut and press enter. Then check your "C:\Program Files\OpenVPN\config" folder for new file key.txt.
- 2.1.2. Open "C:\Program Files\OpenVPN\config" and create file "static.ovpn" with content as in example:



- 2.1.2.1. In line remote write your server IP address.
- 2.1.2.2. In line ifconfig write your virtual remote and local IP address as in example in 1.4.6 item.
- 2.1.2.3. The last line is the name of your static OpenVPN key, which you generated and have (it should stay here) in "C:\Program Files\OpenVPN\config" folder.




2.2. Configure Rut500 as a server

- 2.2.1. Open RUT500 web GUI and select services -> OpenVPN
- 2.2.2. Create new configuration file by selecting role "server" and typing configuration name which you like. Then press Add New button.



2.2.3. After that you will see a line with your tunnel. Press edit button to configure server.





2.3. Connect to server

2.3.1. After that open application "OpenVPN GUI". It should be already installed in your computer as bundle of "OpenVPN windows installer". Then you will see this "

" two computers with red displays. Press on it with right mouse button and select "Connect".