

**HUAWEI B618s-22d LTE CPE
V100R001**

Product Description

Issue	02
Date	2016-11-08

HUAWEI TECHNOLOGIES CO., LTD.



Copyright © Huawei Technologies Co., Ltd. 2016. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions



and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base
Bantian, Longgang
Shenzhen 518129
People's Republic of China

Website: <http://consumer.huawei.com/en/>

Email: mobile@huawei.com

About This Document

Summary

This document provides information for product features, main functions and services, technical specifications and technical references.

This document includes:

Chapter	Details
1 Product Overview	Describes the appearance and main services of product
2 Features	Describes the product features
3 Technical Specifications	Describes the specifications of product hardware, software and user interface
4 Services and Applications	Describes the main functions and applications
5 System Structure	Describes the product system structure
6 Packing List	Describes the devices and accessories of the product



NOTE

The document is an invitation to offer but not an offer. It is intended to describe the general features and functions of products. The features and functions of certain products vary with requirements of customers.

History

Issue	Date	Details
02	2016-11-08	Modify the product picture silk screen, consistent with the actual, the second release.
01	2016-07-14	Initial official release.

Contents

About This Document	ii
1 Product Overview	1
2 Features	3
3 Technical Specifications	4
3.1 Hardware Specifications	4
3.2 Antenna and Radio Frequency Specifications	6
3.3 Software Specifications	9
4 Services and Applications	12
4.1 Data Services	12
4.1.1 Accessing the Internet Through a Mobile Network (LTE/UMTS/GSM)	12
4.1.2 Accessing the Internet Through an Ethernet Network	14
4.2 Voice Services	14
4.3 SMS	15
4.4 Security Service	15
4.5 Local management and maintenance	16
5 System Structure	17
5.1 System Architecture Diagram	17
5.2 Functional Modules	17
6 Packing List	18
A Acronyms and Abbreviations	19

1 Product Overview

The HUAWEI B618s-22d LTE CPE (B618s-22d for short) is a wireless gateway that integrates LTE and high-speed Ethernet uplink access, which provides users with flexible and diversified data access and voice services.



NOTE

The frequency bands of the product are as follows.

B618s-22d support:

- LTE: B1/3/7/8/20/38
FDD: 2100 MHz/1800 MHz/2600 MHz/ 900 MHz/800 MHz
TDD: 2600 MHz
Intra-band contiguous: CA_1C,CA_3C,CA_7C,CA_8B, CA_38C
Inter-band:
CA_1A-3A,CA_1A-20A,CA_3A-7A,CA_3A-20A,CA_7A-20A,CA_20A-38A
- DC-HSPA+/HSPA+/HSPA/UMTS: Band 1/8 2100MHz/900MHz
- EDGE/GPRS/GSM: Band 2/3/5/8 1900MHz/1800MHz/850MHz/900MHz

The B618s-22d supports the following standards:

- LTE (Long Term Evolution)
- DC-HSPA+ (Dual Carrier High Speed Packet Access Plus)
- HSPA+ (High Speed Packet Access Plus)
- HSUPA (High Speed Uplink Packet Access)
- HSDPA (High Speed Downlink Packet Access)
- UMTS (Universal Mobile Telecommunications System)
- EDGE (Enhanced Data Rates for Global Evolution)
- GPRS (General Packet Radio Service)
- GSM (Global System for Mobile Communications)

The B618s-22d supports wired and wireless network access, and provides data routing service.

The B618s-22d provides the following services:

- Data service
- Voice service
- SMS
- Security service
- Local maintenance management function

Figure 1-1 B618s-22d appearance



Z

2 Features

The B618s-22d mainly supports the following features:

- Access to LTE wireless networks
- Access to Gigabit Ethernet networks
- High-speed data access
 - LTE FDD: 4*4MIMO+2CA 582Mbps
 - LTE TDD: 4*4MIMO+2CA 426Mbps
 - DC-HSPA+: DL 42 Mbit/s, UL 5.76 Mbit/s
 - HSPA+: DL 21 Mbit/s (64QAM) / 28 Mbit/s (MIMO), UL 5.76 Mbit/s
 - HSPA: DL 14.4 Mbit/s, UL 5.76 Mbit/s
 - WCDMA PS: 384 kbit/s
 - EDGE: DL 296 kbit/s, UL 236.8 kbit/s
 - GPRS: 85.6 kbit/s
- Complies with wireless 802.11b/g/n standards with data rates up to 300 Mbit/s
- Complies with wireless 802.11a/ac standards with data rates up to 1300 Mbit/s
- SMS
- IPv4 /IPv6 dual stack
- Compatibility with RJ11 telephone ports; support VoLTE voice(customizable function), can be set to Voice over Internet Protocol (VoIP) voice mode or Circuit Switch (CS) voice mode
- External LTE antenna port
- Support for Huawei HiLink App
- WPS 2.0
- HOTA updates
- Built-in DHCP Server, DNS RELAY and NAT
- Security services. Provides instant protection to block potential security risks and intrusion attempts
- Windows 7, Windows 8, Windows 8.1, Windows 10 (does not support Windows RT), MAC OS X 10.7, 10.8, 10.9 and 10.10 with latest upgrades
- User-friendly design of LED indicator. Easy to observe the status of equipment.

3 Technical Specifications

3.1 Hardware Specifications

Table 3-1 Technical specifications of the B618s-22d main unit

Item	Description	
Technical standard	WAN	LTE/DC-HSPA+/HSPA+/HSPA/UMTS/EDGE/GPRS/GSM
	LAN	IEEE 802.3/802.3u
	WLAN	IEEE 802.11a/b/g/n/ac
Working frequency band	LTE	B618s-22d support: LTE: B1/3/7/8/20/38 FDD: 2100 MHz/1800 MHz/2600 MHz/900 MHz/800 MHz TDD: 2600 MHz Intra-band contiguous: CA_1C,CA_3C,CA_7C,CA_8B, CA_38C Inter-band: CA_1A-3A,CA_1A-20A,CA_3A-7A,CA_3A-20A,CA_7A-20A,CA_20A-38A
	DC-HSPA+/HSPA+/HSPA/UMTS	Band 1/8 2100 MHz /900 MHz
	EDGE/GPRS/GSM	Band 2/3/5/8 1900 MHz/1800 MHz/850 MHz/900 MHz
	WLAN	• 2.4GHz 2.400 GHz~2.474 GHz • 5GHz 5.150GHz~5.350GHz&5.470GHz~5.725GHz

Item	Description		
External port	<ul style="list-style-type: none"> One power adapter port One LAN port (RJ45) One LAN/WAN port (RJ45) One phone port (RJ11) Two external LTE antenna ports (TS-9) One micro-SIM card slot One USB 2.0 port (Supports a maximum of 500mA current) 		
Antenna	<ul style="list-style-type: none"> Built-in LTE/UMTS/GSM primary antenna Built-in LTE/UMTS secondary antenna Built-in WLAN 2.4G antenna Built-in WLAN 5G antenna 		
Indicator	<ul style="list-style-type: none"> One power indicator One Internet status indicator One Mode indicator One WLAN/WPS indicator One LAN indicator One group of signal strength indicators 		
Button	<ul style="list-style-type: none"> One Power ON or OFF switch One WPS button One Reset button 		
Maximum transmit power	LTE	Conform to 3GPP Power Class 3 Definition	
	WLAN	2.4G	802.11b 16 dBm
			802.11g 17 dBm
			802.11n 17 dBm
	5G	Low band	802.11a 16 dBm
			802.11n 16 dBm
			802.11ac 16 dBm
		Middle band	802.11a 16 dBm
			802.11n 16 dBm
			802.11ac 16 dBm
		High band	802.11a 20 dBm
			802.11n 20 dBm
			802.11ac 20 dBm

Item	Description	
Receiving sensitivity	LTE	Conform to 3GPP Definition
	UMTS	Conform to 3GPP Definition
	GSM	-104 dBm
	WLAN	802.11a: -71 dBm (54 Mbit/s)
		802.11b: -85 dBm (11 Mbit/s)
		802.11g: -71 dBm (54 Mbit/s)
		802.11n: -69 dBm (65 Mbit/s)
		802.11ac: -65 dBm (78 Mbit/s)
Power consumption	< 24W	
AC/DC power supply	<ul style="list-style-type: none"> AC: 100 V - 240 V DC: 12 V/2 A 	
Dimensions (Maximum)	95mm × 95mm × 208mm	
Weight	About 700g (excluding the power adapter)	
Temperature	<ul style="list-style-type: none"> Working temperature: 0°C to 40°C Storage temperature: -20°C to +70°C 	
Humidity	5% - 95%	

3.2 Antenna and Radio Frequency Specifications

Table 3-2 LTE main diversity antenna specifications

Item	Description
Frequency	703 MHz~960 MHz/1710 MHz~2690 MHz
Input impedance	50 Ω
Standing wave ratio	< 3
Efficiency	≥ -4.5dB@703MHz~960MHz ≥ -3.5dB@1710MHz~2690MHz
H side gain	≥ 1dBi
Polarization	Linear polarization

Table 3-3 LTE secondary antenna specifications

Item	Description
Frequency	758MHz~960MHz/1710MHz~2690MHz
Input impedance	50 Ω
Standing wave ratio	< 4
Efficiency	$\geq -5.5\text{dB}@703\text{MHz}\sim 960\text{MHz}$ $\geq -4\text{dB}@1710\text{MHz}\sim 2690\text{MHz}$
H side gain	$\geq 0\text{dBi}$
Polarization	Linear polarization

Table 3-4 WLAN 2.4 GHz antenna specifications

Item	Description
Frequency	2.400 GHz~2.474 GHz
Input impedance	50 Ω
Standing wave ratio	< 2
Efficiency	$\geq -3\text{dB}$
H side gain	$\geq 1\text{dBi}$
Polarization	Linear polarization

Table 3-5 WLAN 5 GHz antenna specifications

Item	Description
Frequency	5.15-5.35GHz / 5.47-5.725GHz
Input impedance	50 Ω
Standing wave ratio	<2
Efficiency	$\geq -3\text{dB}$
H side gain	$\geq 1\text{dBi}$
Polarization	Linear polarization

Table 3-6 External antenna specifications



NOTE

- The external antenna is an optional accessory. Signals may be weak in some areas; thus, you can choose whether to use the external antenna.
- The external antenna can be used indoor only. Put it near the window when using to get better signal.
- Avoid thunderstorms when using.

Item	Description
Technical standard	LTE/DC-HSPA+/HSPA+/HSPA/WCDMA/EDGE/GPRS/GSM
Frequency	<ul style="list-style-type: none">• 703 MHz - 960 MHz• 1710 MHz - 2690 MHz
Input impedance	50 Ω
Standing wave ratio	< 3
H side gain	≥ 1 dBi (horizontal level)
Polarization	Linear polarization
Interface standard	TS-9

3.3 Software Specifications

Table 3-7 Software specifications

Item	Description	
Gateway	Supports the default route: 0.0.0.0.	
	Supports the default gateway address: 192.168.8.1.	
	Supports the Address Resolution Protocol (ARP).	
	Supports the Internet Control Message Protocol (ICMP).	
	Supports the domain name service (DNS).	
	NAT	Supports NAT and Network Address and Port Translation (NAPT), which complies with RFC2663, RFC3022, and RFC3027.
		Supports CONE NAT.
		Supports fragmented message identification during common NAT.
	DHCP server	Enables and disables the DHCP server.
		Configures DHCP server address pools.
		Sets the lease time.
VPN client	Support L2TP VPN client (When L2TP vpn client function is enabled, the throughput performance will slow down, the maximum speed can up to 50Mbps (dependent on network environment).)	
SMS	Writing/Sending/Receiving	
	Writing/Sending/Receiving extra-long messages	
Voice	VoIP	Supports the Session Initiation Protocol (SIP).
		Supports G.711a/G.711u/G.726 (-24/-32)/G.722 for encoding and decoding.
	CS voice	Supports CS voice communication over UMTS and GSM networks.
		Supports the circuit switched fallback (CSFB).
	VoLTE voice	Customizable function
Firewall	Enables and disables the firewall.	
	Filters LAN MAC addresses.	
	Filters LAN IP addresses.	

Item	Description	
	Filters URLs.	
	Supports demilitarized zone (DMZ).	
	Supports Universal Plug and Play (UPnP).	
	Supports Application Level Gateway (ALG).	
WLAN	Broadcasts and hides service set identifiers (SSIDs).	
	Complies with IEEE 802.11 a/b/g/n/ac.	
	Supports WPS	
	Authentication	Supports OpenSystem authentication.
		Supports encryption using wired equivalent privacy (WEP), Wi-Fi protected access preshared key (WPA /WPA2-PSK), and WPA2-PSK authentication.
		Supports the Advanced Encryption Standard (AES) encryption algorithm.
		Supports the TKIP and AES hybrid encryption algorithm.
	MAC address authentication	Supports the MAC address authentication whitelist.
		Supports the MAC address authentication blacklist.
		Supports a maximum of 10 MAC address entries.
	Supports automatic transmission rate adjustment.	
	Station management	Supports station status queries.
		Supports a maximum of 32+32 connected stations.
IPv6/IPv4 dual stack	DHCPv6/v4 server and client	
	DNSv6/v4 server and client	
	Display IPv6/v4 WAN address	
HUAWEI HiLink App	View the data traffic usage and SMS.	
	Manage the connected devices.	
	Change CPE's SSID and password.	
System requirements	Operating system: Windows 7, Windows 8, Windows 8.1, Windows 10 (does not support Windows RT), MAC OS X 10.7, 10.8, 10.9 and 10.10 with latest upgrades	

Item	Description
	Hardware configuration: meets the configuration requirements of the operating system.

4 Services and Applications


4.1 Data Services

The B618s-22d can access the Internet through mobile networks, and Ethernet networks. By connecting to the B618s-22d using Wi-Fi or a network cable, users can get access to high-speed Internet services and establish a local area network (LAN).

4.1.1 Accessing the Internet Through a Mobile Network (LTE/UMTS/GSM)

The B618s-22d can access the Internet through mobile networks.


Figure 4-1 Accessing the Internet through a mobile network



4.1.2 Accessing the Internet Through an Ethernet Network

Connect the B618s-22d's LAN/WAN port to a wall-mounted Ethernet port using a network cable.


Figure 4-2 Accessing the Internet through an Ethernet network



4.2 Voice Services

The B618s-22d provides one telephone port that can be connected to telephones for calling.

Figure 4-3 Connecting telephones to the B618s-22d



4.3 SMS

The B618s-22d supports message writing/sending/receiving and group sending (up to 50 contacts at a time). You can manage messages through the Web page, such as inbox, outbox, draft.

4.4 Security Service

The B618s-22d supports various security features, such as the firewall, user authentication, and PIN protection, protect users against security threats from the Internet when users are using network services.


4.5 Local management and maintenance

The B618s-22d supports local configuration through the Web page. You can accomplish device management, network configuration and ensure normal and stable performance.

5 System Structure

5.1 System Architecture Diagram

Figure 5-1 System architecture



5.2 Functional Modules

- Mobile network access: The B618s-22d adopts the LTE/UMTS/GSM access technology at the WAN side, can access the wireless broadband packet-based.
- WLAN AP function: 802.11 a/b/g/n/ac compliant WLAN AP interface is provided, used for wireless networking at home. The interface is compliant with the IEEE 802.11 a/b/g/n/ac standard and the WPA/WPA2-PSK/WPA2-PSK/WEP security authentication.
- DHCP/DNS: The DHCP server dynamically allocates IP addresses to PCs. The DNS parses domain names.
- Web management: You can configure, modify and query the configuration information of the B618s-22d.
- Routing and NAT: High-speed routing capability. With the built-in NAT, the B618s-22d, together with wireless broadband packet-based network devices, can provide flexible broadband access solutions and networking schemes.

6 Packing List

Table 6-1 Packing list

Description	Quantity	Remarks
Wireless Gateway	1	Standard
Power supply adapter	1	Standard
Quick Start	1	Standard
Ethernet cable	1	Standard
Warranty card	1	Optional
Phone cable	1	Optional

HUAWEI B618s-22d wireless gateway also provide external antenna as optional for you to choose.

A

Acronyms and Abbreviations

A	
AC	Alternating Current
ARP	Address Resolution Protocol
AP	Access Point
APN	Access Point Name
C	
CPE	Customer Premises Equipment
CS	Circuit Switch
CSFB	Circuit Switched Fallback
D	
DHCP	Dynamic Host Configuration Protocol
DL	Downlink
DNS	Domain Name Server
G	
GE	Gigabit Ethernet
H	
HSPA	High Speed Packet Access
HSPA+	High Speed Packet Access Plus
HSDPA	High Speed Downlink Packet Access
HSUPA	High Speed Uplink Packet Access
I	
IP	Internet Protocol
ICMP	Internet Control Message Protocol

A	
L	
LAN	Local Area Network
LED	Light Emitting Diode
LTE	Long Term Evolution
M	
MCS	Modulation and Coding Scheme
N	
NAT	Network Address Translation
P	
POTS	Plain Old Telephone Service
T	
TKIP	Temporal Key Integrity Protocol
U	
UMTS	Universal Mobile Telecommunications System
UL	Uplink
V	
VoIP	Voice over Internet Protocol
W	
WAN	Wide Area Network
WLAN	Wireless Local Area Network
WCDMA	Wideband Code Division Multiple Access
Wi-Fi	Wireless Fidelity